

# Product data sheet

## Roller guide rail Slimdrive EMD / EMD-F / EMD Invers



for door leaf installation on the hinge side

### AREAS OF APPLICATION

- Single and double leaf swing doors
- Door opening angle up to 115°
- Reveal depth up to 50 mm

# Roller guide rail Slimdrive EMD / EMD-F / EMD Invers



## PRODUCT FEATURES

- Length 760 mm
- Colour EV1 or acc. to RAL
- Compatible with integrated opening restrictor

## TECHNICAL DATA

Productname	Roller guide rail Slimdrive EMD / EMD-F / EMD Invers
Height	20 mm
Width	760 mm
DIN left	Yes
DIN right	Yes
Suitability for fire protection doors	Yes

## VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Type of installation
Roller guide rail Slimdrive EMD	for door leaf installation (Slimdrive EMD-F / EMD Invers). DIN right, length 760 mm	106803	according to RAL	Door leaf installation, DIN right
Roller guide rail Slimdrive EMD	for door leaf installation (Slimdrive EMD-F / EMD Invers). DIN right, length 760 mm	106798	silver-coloured	Door leaf installation, DIN right
Roller guide rail Slimdrive EMD	for door leaf installation (Slimdrive EMD / EMD-F / Invers), left-hand (ISO 6)	106797	according to RAL	Door leaf installation, DIN left
Roller guide rail Slimdrive EMD	with deeper guide, for door leaf installation (Slimdrive EMD-F / EMD Invers), DIN right, length 760 mm, 30 x 30 mm	133245	silver-coloured	Door leaf installation
Roller guide rail Slimdrive EMD	for door leaf installation (Slimdrive EMD / EMD-F / Invers), left-hand (ISO 6)	106742	silver-coloured	Door leaf installation, DIN left
Roller guide rail Slimdrive EMD	with deeper guide, for door leaf installation (Slimdrive EMD-F / EMD Invers), DIN left, length 760 mm, 30 x 30 mm	133244	silver-coloured	Door leaf installation