

# Product data sheet Closer body TS 1500 G \*



Main body for overhead door closer with guide rail EN 1

## AREAS OF APPLICATION

- ightarrow Right and left single-action doors
- ightarrow Single-action doors up to 750 mm leaf width
- ightarrow Door leaf installation hinge side and transom installation opposite hinge side

# Product data sheet | Page 2 of 3 Closer body TS 1500 G \*



### **PRODUCT FEATURES**

- ightarrow Closing speed can be adjusted from the side via valve
- ightarrow Latching action can be adjusted from the side via valve
- ightarrow Door closer, can be used for right and left hand doors

#### TECHNICAL DATA

Productname	Closer body TS 1500 G * EN 1 750 mm		
Closing force in accordance with EN 1154			
Leaf width (max.)			
Type of installation	Door leaf installation hinge side, Transom installation opposite hir side		
Opening angle (max.)	180 °		
Identical design for DIN left and DIN right	Yes		
Length	177 mm		
Width	39 mm		
Height	50 mm		
Closing force adjustable	No		
Adjustable closing speed	Yes		
Latching action adjustable	Yes, via valve		
Back check integrated	No		
Smoke switch integrated	No		

#### VARIANTS / ORDER INFO

Designation	Description	ldent- No.	Colour	Closing force in accordance with EN 1154	Dimensions
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	silver-coloured	EN 1	177 x 39 x 50 mm
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	white RAL 9016	EN 1	177 x 39 x 50 mm
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	according to RAL	EN 1	177 x 39 x 50 mm
GEZE TS 1500 G closer *	Size EN 1 (without guide rail and lever)	N/A	dark bronze	EN 1	177 x 39 x 50 mm

# Product data sheet | Page 3 of 3 Closer body TS 1500 G \*



\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.