

Product data sheet

SCT stainless steel *



Key switch stainless steel for authorised activation and for changing the mode of operation of automatic doors

AREAS OF APPLICATION

- For authorised activation of automatic doors
- For authorised changing of the mode of operation on automatic doors
- Suitable for exterior and interior use



PRODUCT FEATURES

- Robust metal housing
- Anti-burglar by mechanical security system
- IP rating IP54

TECHNICAL DATA

Productname	SCT stainless steel *
IP rating	IP54

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
Key switch, switching operation without Euro profile half cylinder	Mounting with claws or screws, one-sided switching operation (key can be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	098870	silver-coloured	79 x 79 x 12.5 mm	Flush-mounted installation
Key switch with Euro profile half cylinder and three keys	adjustable stay-put or switching operation on both sides (key can be pulled out in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	137056	silver-coloured		Surface-mounted installation
Key switch, stay-put without Euro profile half cylinder	Attachment with claws or screws, stay-put on one side (key can be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	111357	silver-coloured	79 x 79 x 12 mm	Flush-mounted installation

ACCESSORIES

EURO PROFILE HALF CYLINDER 40 MM

with Euro profile half cylinder and 3 keys

Designation	Description	Ident-No.	Colour	Type of installation
Euro profile half cylinder 40 mm	Division (10/30) with three keys, keyed to differ, for key switch SCT and MBZ Control cabinet lock	090176	silver-coloured	Integrated

SCT stainless steel *



* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.