

# Product data sheet

# GEZE ActiveStop

# integrated



Door damper on both sides for interior wooden swing doors

## AREAS OF APPLICATION

- Right and left timber single-action doors indoors
- Room doors with high access convenience
- Single-action doors up to 1100 mm leaf width
- Integrated installation in the door leaf
- Barrier-free access in accordance with DIN 18040-2

**PRODUCT FEATURES**

- Door opening angle with variable adjustment from 80°-140°
- Can be used for right and left hand doors without conversion
- Soft opening and closing of doors up to max. 45 kg leaf weight
- Gentle stopping, quiet closing and comfortable keeping open of doors
- Practically eliminates slamming doors, trapped fingers, and damage to walls and furniture
- Secure holding of the door when open, meaning no door stopper necessary
- Opening and latching speed when installed can be set via a valve
- Integrated safety valve offers overload protection

**TECHNICAL DATA**

Productname	GEZE ActiveStop integrated
Depth	28 mm
Height	64 mm
Leaf weight (max.)	45 kg
Leaf width (max.)	1100 mm
Category of door	flush-mounted, rebated
Leaf thickness from	38 mm
Identical design for DIN left and DIN right	Yes
Rebate space	approx. 6 mm clearance in handle area
Installation type	concealed
Adjustable draw-in damper	Yes, via valve
Draw-in damper in direction of closing movement from	25 °
Free swing area	25 ° - 60 °
Draw-in damper in direction of opening movement from	60 °
Adjustable door opening angle	Yes, stepless
Hold-open position adjustable	80 ° - 140 °
Safety valve against overload	Yes

**VARIANTS / ORDER INFO**

Designation	Description	Ident-No.	Colour	Dimensions	Installation type
GEZE ActiveStop integrated	Door damper on both sides for interior wooden swing doors	163411	silver-coloured	286 x 32 x 45 x 28 mm	concealed

**ACCESSORIES****MILLING EDGE COVER \***

For covering the milling edge of rebated doors



Designation	Description	Ident-No.	Colour
Milling edge cover *	10 pieces, to cover the milling edge on rebated doors	169724	white RAL 9016
Milling edge cover *	10 pieces, to cover the milling edge on rebated doors	169725	grey RAL 7035
Milling edge cover	10 pieces, to cover the milling edge on rebated doors	170264	according to RAL

**MILLING FIXTURE \***

For milling door leaves and frames for the GEZE ActiveStop integrated



Designation	Description	Ident-No.
Milling fixture *	For the processing of the door leaf and frame with a commercially available router; contains templates for guide rail and basic body milling for the GEZE ActiveStop integrated	166886

**GUIDE RAIL FIXING PLATES**

For fixing the concealed horizontally installed guide rail if there is insufficient screw depth



Designation	Description	Ident-No.
Fastening strips for guide rails	For fastening the integrated guide rail in the in timber frames with insufficient screw-in depth of fixing screws	165814

## GEZE ActiveStop integrated



---

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.