

Product data sheet

Levolan 60 glass ceiling installation concealed



Sliding door fitting for 60 kg glass leafs and concealed ceiling
installation



Levolan 60 glass ceiling installation concealed

AREAS OF APPLICATION

- For design-oriented interior sliding doors for living and office areas
- For all single- and multiple-leaf sliding doors
- Attachment to the ceiling within a concealed installation
- For attachment on the wall and ceiling (directly and concealed) as well as for glass installation
- Damped on one or both sides with Levolan 60 SoftStop
- Smooth running with Levolan 60 SoftStop makes it particularly well suited for doors in living and office spaces

PRODUCT FEATURES

- Design sliding door fitting system for glass doors with ESG (toughened safety glass) 8 to 12 mm as well as LSG up to 10.76 mm and up to 60 kg leaf weight
- Slim design with integrated door fitting technology
- Fully integrated in the track
- The Levolan Smart fix installation system means the use of assembly tools is reduced to a minimum – for quick and convenient installation
- Final assembly of the door fitting by simple clipping
- With damping on one or both sides for doors with up to 60 kg leaf weight, so that the door is quietly slowed down and moved automatically into the end position
- Tested for durability in accordance with DIN EN 1527 over 100,000 test cycles
- Cover profiles for ceiling installation enable an elegant connection between the ceiling opening and the door fitting

TECHNICAL DATA

Productname

Levolan 60 glass ceiling installation concealed

Levolan 60 glass ceiling installation concealed

PART

LSG GLASS / METAL GLUE *

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

LEVOLAN 60 COMPLETE SET

Levolan sliding door fitting for leaf weights up to 60 kg



Designation	Description	Ident-No.	Colour	Leaf width (min.)	Leaf width (max.)
Levolan 60 complete set	For wall installation	147169	Stainless steel optic	400 mm	1240 mm
Levolan 60 complete set	For wall installation	147166	EV1	400 mm	1240 mm
Levolan 60 complete set	For wall installation	147167	Stainless steel optic	400 mm	840 mm
Levolan 60 complete set	For wall installation	147164	EV1	400 mm	840 mm
Levolan 60 complete set	For wall installation	147165	EV1	400 mm	1040 mm
Levolan 60 complete set	For wall installation	147168	Stainless steel optic	400 mm	1040 mm

ACCESSORIES

SPACER PROFILE FOR WALL CLEARANCE LEVOLAN 60 / 120

Spacer profile for wall installation of Levolan 60/120



Designation	Description	Ident-No.	Colour
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157993	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147571	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147557	EV1
Spacer profile for wall clearance Levolan 60 / 120 *	10 mm additional space, can be stacked up to 20 mm	147559	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147572	Stainless steel optic

Levolan 60 glass ceiling installation concealed

Designation	Description	Ident-No.	Colour
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147558	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm / bespoke configuration	147573	
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157991	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147560	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147556	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147555	EV1

LEVOLAN SOFTSTOPDUO SET, DAMPED ON BOTH SIDES, UP TO 100 KG

Levolan SoftStopDuo draw-in damping on both sides for leaf weights up to 100 kg



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan SoftStopDuo set, damped on both sides, up to 100 kg	for draw-in damping left & right, consisting of: 1 x double damping unit, 2 x spacers - Levolan 60 and 2 x spacers - Levolan 120 for cover panel bracket, 2 x adjustable triggers, can also be retrofitted - for Levolan 60 minimum leaf width 770 mm, for Levolan 120 minimum leaf width 1010 mm	146402	770 mm	1240 mm

LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop draw-in damping on one side left version



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	for draw-in damping left, consisting of: 1 x damping unit, 1 x spacer for cover panel bracket, 1 x trigger, can also be retrofitted - minimum leaf width 570 mm	146370	570 mm	1240 mm

Levolan 60 glass ceiling installation concealed

LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop draw-in damping on one side right version



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	for draw-in damping right, consisting of: 1 x damping unit, 1 x spacer for cover panel bracket, 1 x trigger, can also be retrofitted - minimum leaf width 570 mm	146401	570 mm	1240 mm

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.